



**NOTES:**

1. LOCATIONS OF EXISTING UTILITIES MUST BE FIELD LOCATED WITH THEIR RESPECTIVE OWNERS BEFORE DIGGING OR MAKING NEW CONNECTIONS. "CALL 811 BEFORE YOU DIG."
2. SANITARY SEWER CAN VARY 4' FROM CENTERLINE AROUND CURVES, HOWEVER MINIMUM SEPARATION DISTANCES MUST BE MET.
3. WATER AND SEWER LATERALS SHALL BE STUBBED OUT TO FAR SIDE OF THE RIGHT OF WAY.
4. STREET LIGHTING SHALL BE AT EACH INTERSECTION AND MID-BLOCK WITH A MAXIMUM SPACING OF 350' BETWEEN LIGHT POLES.
5. UTILITY POLES, FIRE HYDRANTS, LIGHT POLES AND STREET SIGNS SHALL BE LOCATED WITH 1.5' MINIMUM CLEARANCE FROM BACK OF CURB TO CLOSEST FACE OF UTILITY AND SHALL NOT BE PLACED INTO SIDEWALK. UTILITY LOCATIONS SHALL CONFORM TO THE LATEST EDITION OF THE MUTCD.
6. STREET TREES SHALL BE OF THE TYPE AND IN THE LOCATION AS APPROVED BY THE CITY URBAN FORESTER.
7. CORNER RADIUS (SEE DRAWING SD-10, CORNER RADIUS)

CITY OF WATFORD CITY, NORTH DAKOTA PUBLIC WORKS DEPARTMENT	
<b>URBAN MINOR ARTERIAL STREET                  UTILITY LOCATIONS</b>	
APPROVED FOR PUBLICATION _____ City Engineer	DWG. NO.  <b>SD-3</b>
_____ Date	